

**Information requirements  
(air-to-air air conditioners)**

Model(s):GMV-Q335WM/E-X							
Outdoor side heat exchanger of air conditioner	air						
Indoor side heat exchanger of air conditioner	air						
Type	compressor driven vapour compression						
If applicable: driver of compressor	electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	33.50	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	311.4	%
Declared cooling capacity for part load at given outdoor temperatures $T_j$ and indoor 27°/19 °C (dry/wet bulb)				Declared energy efficiency ratio for part load at given outdoor temperatures $T_j$			
$T_j = + 35 \text{ °C}$	$P_{dc}$	33.70	kW	$T_j = + 35 \text{ °C}$	$EER_d$	3.05	-
$T_j = + 30 \text{ °C}$	$P_{dc}$	25.07	kW	$T_j = + 30 \text{ °C}$	$EER_d$	5.09	-
$T_j = + 25 \text{ °C}$	$P_{dc}$	15.57	kW	$T_j = + 25 \text{ °C}$	$EER_d$	9.60	-
$T_j = + 20 \text{ °C}$	$P_{dc}$	7.18	kW	$T_j = + 20 \text{ °C}$	$EER_d$	22.60	-
Degradation co-efficient for air conditioners(*)	$C_{dc}$	0.25	—				-
Power consumption in modes other than ‘active mode’							
Off mode	$P_{OFF}$	0.019	kW	Crankcase heater mode	$P_{CK}$	0.049	kW
Thermostat-off mode	$P_{TO}$	0.01	kW	Standby mode	$P_{SB}$	0.019	kW
Other items							
Capacity control	variable			For air-to-air air conditioner: air flow rate, outdoor measured	—	14000	$m^3/h$
Sound power level, indoor/outdoor	$L_{WA}$	-/80	dB				
If engine driven: Emissions of nitrogen oxides	$NO_x(**)$	-	mg/kWh fuel input GCV				
GWP of the refrigerant	2088		kg CO <sub>2</sub> eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of manufacturer: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*) If $C_{dc}$ is not determined by measurement then the default degradation coefficient air conditioners shall be 0,25. (**) From 26 September 2018. Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							

**Information requirements  
(heat pump)**

Model(s):GMV-Q335WM/E-X							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	23.57	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	195.0	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature $T_j$				Declared coefficient of performance for part load at given outdoor temperatures $T_j$			
$T_j = -7\text{ °C}$	$P_{dh}$	20.85	kW	$T_j = -7\text{ °C}$	$COP_d$	2.78	-
$T_j = +2\text{ °C}$	$P_{dh}$	14.22	kW	$T_j = +2\text{ °C}$	$COP_d$	4.39	-
$T_j = +7\text{ °C}$	$P_{dh}$	9.41	kW	$T_j = +7\text{ °C}$	$COP_d$	8.29	-
$T_j = +12\text{ °C}$	$P_{dh}$	11.09	kW	$T_j = +12\text{ °C}$	$COP_d$	10.86	-
$T_{biv} =$ bivalent temperature	$P_{dh}$	20.85	kW	$T_{biv} =$ bivalent temperature	$COP_d$	2.78	-
$T_{OL} =$ operation limit	$P_{dh}$	19.98	kW	$T_{OL} =$ operation limit	$COP_d$	2.78	-
$T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$ )	$P_{dh}$	-	kW	$T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$ )	$COP_d$	-	-
Bivalent temperature	$T_{biv}$	-7	°C	Operation limit temperature	$T_{ol}$	-10	°C
Degradation co-efficient heat pumps(**)	$C_{dh}$	0.25	—				
Power consumption in modes other than 'active mode'				Supplementary heater			
Off mode	$P_{OFF}$	0.019	kW	Back-up heating capacity (*)	$el_{bu}$	-	kW
Thermostat-off mode	$P_{TO}$	0.013	kW	Type of energy input	-		
Crankcase heater mode	$P_{CK}$	0.049	kW	Standby mode	$P_{SB}$	0.019	kW
Other items							
Capacity control	variable			For air-to-air heat pumps: air flow rate, outdoor measured	—	14000	m <sup>3</sup> /h
Sound power level, indoor/outdoor measured	$L_{WA}$	-/86	dB				
Emissions of nitrogen oxides (if applicable)	$NO_x(***)$	-	mg/kWh input GCV	Rated brine or water flow rate, outdoor side heat exchanger	—	-	m <sup>3</sup> /h
GWP of the refrigerant	2088		kg CO <sub>2</sub> eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of manufacturer: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*)							
(**) If $C_{dh}$ is not determined by measurement then the default degradation coefficient of heat pumps shall be 0,25.							
(***) From 26 September 2018.							
Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							