

**Information requirements
(air-to-air air conditioners)**

Model(s):GMV-S120WL/A-S							
Outdoor side heat exchanger of air conditioner	air						
Indoor side heat exchanger of air conditioner	air						
Type	compressor driven vapour compression						
If applicable: driver of compressor	electric motor						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated cooling capacity	$P_{rated,c}$	12.1	kW	Seasonal space cooling energy efficiency	$\eta_{s,c}$	318.9	%
Declared cooling capacity for part load at given outdoor temperatures T_j and indoor 27 °/19 °C (dry/wet bulb)				Declared energy efficiency ratio for part load at given outdoor temperatures T_j			
$T_j = + 35$ °C	P_{dc}	12.51	kW	$T_j = + 35$ °C	EER_d	4.59	-
$T_j = + 30$ °C	P_{dc}	8.89	kW	$T_j = + 30$ °C	EER_d	7.33	-
$T_j = + 25$ °C	P_{dc}	7.44	kW	$T_j = + 25$ °C	EER_d	12	-
$T_j = + 20$ °C	P_{dc}	7.21	kW	$T_j = + 20$ °C	EER_d	19.03	-
Degradation co-efficient for air conditioners(*)	C_{dc}	0.25	-				-
Power consumption in modes other than 'active mode'							
Off mode	P_{OFF}	0.043	kW	Crankcase heater mode	P_{CK}	0.043	kW
Thermostat-off mode	P_{TO}	0.005	kW	Standby mode	P_{SB}	0.043	kW
Other items							
Capacity control	variable			For air-to-air air conditioner: air flow rate, outdoor measured	-	6000	m^3/h
Sound power level, indoor/outdoor	L_{WA}	-71	dB				
If engine driven: Emissions of nitrogen oxides	$NO_x(**)$	-	mg/kWh fuel input GCV				
GWP of the refrigerant	2088		kg CO ₂ eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070	Name of manufacturer: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI						
(*) If C_{dc} is not determined by measurement then the default degradation coefficient air conditioners shall be 0,25. (**) From 26 September 2018. Where information relates to multi-split air conditioners, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							

**Information requirements
(heat pump)**

Model(s): GMV-S120WL/A-S							
Outdoor side heat exchanger of heat pump	air						
Indoor side heat exchanger of heat pump	air						
Indication if the heater is equipped with a supplementary heater	no						
If applicable: driver of compressor	electric motor						
Parameters declared for	Average climate condition						
Item	symbol	value	unit	Item	symbol	value	unit
Rated heating capacity	$P_{rated,h}$	14.0	kW	Seasonal space heating energy efficiency	$\eta_{s,h}$	166.9	%
Declared heating capacity for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance part load at given outdoor temperatures T_j			
$T_i = -7$ °C	P_{dh}	10.95	kW	$T_i = -7$ °C	COP_d	2.7	-
$T_i = +2$ °C	P_{dh}	6.72	kW	$T_i = +2$ °C	COP_d	3.98	-
$T_i = +7$ °C	P_{dh}	4.31	kW	$T_i = +7$ °C	COP_d	5.69	-
$T_i = +12$ °C	P_{dh}	4.11	kW	$T_i = +12$ °C	COP_d	7.29	-
T_{biv} = bivalent temperature	P_{dh}	10.95	kW	T_{biv} = bivalent temperature	COP_d	2.7	-
T_{OL} = operation limit	P_{dh}	11.03	kW	T_{OL} = operation limit	COP_d	2.64	-
$T_j = -15$ °C (if $TOL < -20$ °C)	P_{dh}	-	kW	$T_j = -15$ °C (if $TOL < -20$ °C)	COP_d	-	-
Bivalent temperature	T_{biv}	-7	°C	Operation limit temperature	T_{ol}	-10	°C
Degradation co-efficient heat pumps(**)	C_{dh}	0.25	-				
Power consumption in modes other than 'active mode'				Supplementary heater			
Off mode	P_{OFF}	0.043	kW	Back-up heating capacity (*)	$elbu$	-	kW
Thermostat-off mode	P_{TO}	0.048	kW	Type of energy input	-		
Crankcase heater mode	P_{CK}	0.043	kW	Standby mode	P_{SB}	0.043	kW
Other items							
Capacity control	variable			air flow rate, outdoor measured	-	6000	m ³ /h
Sound power level, indoor/outdoor measured	L_{WA}	-/72	dB				
Emissions of nitrogen oxides (if applicable)	$NOx(***)$	-	mg/kWh input GCV	Rated brine or water flow rate, outdoor side heat exchanger	-	-	m ³ /h
GWP of the refrigerant	2088		kg CO2 eq (100 years)				
Contact details: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China, 519070				Name of manufacturer: GREE ELECTRIC APPLIANCES,INC. OF ZHUHAI			
(*)							
(**) If C_{dh} is not determined by measurement then the default degradation coefficient of heat pumps shall be 0,25.							
(***) From 26 September 2018.							
Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of the performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.							